



expanko
Resilient Flooring

180 Gordon Drive | Suite 113 | Exton, PA 19341

PH 610.363.0343 FX 610.363.0735

www.expanko.com

REZTEC AND REZTEC CHUNKS RUBBER FLOORING

RUBBER COMPOUND

TECHNICAL SUPPORT 800.345.6202

Reztec flooring is a unique blend of SBR and EPDM rubber compounds. These two materials when blended together create a wide variety of colors and patterns. The following are details about these two components:

SBR: Styrene-Butadiene Rubber (SBR) is a synthetic rubber most commonly used in tires. All SBR used in Reztec is post consumer tire waste that has been ground and cleaned to remove stones, dirt and metal present in the used tires. Depending upon the color/pattern, Reztec is made of 5% - 100% SBR material.

EPDM: Ethylene Propylene Diene Monomer (EPDM) is synthetic organic elastomer used in a wide variety of industries. The EPDM used in Reztec is a combination of scrap as well as of specification material. Though this material has been rejected for use in other products due to high moisture or other reasons, it is considered first quality for flooring purposes. All EPDM rubber is processed and cleaned to ensure the final flooring product meets our high quality standards. Not only does the use of this type of rubber have environmental benefits, it also ensures competitively priced commercial flooring alternatives.

For more information about Expanko visit our website at www.expanko.com or contact Expanko at 800.345.6202.