



REZTEC AND REZTEC CHUNKS RUBBER FLOORING

Commercial Suitability

Reztec flooring has been designed for use in heavy traffic commercial installations where a resilient, durable and easy to maintain floor is desired. Reztec is made using a high density combination of post consumer, post industrial and virgin rubber. It is available in rolls or tiles and is offered in 4, 6, 8, and 9.5 mm. Reztec is maintained with regular damp mopping and periodic buffing if desired. Expanko recommends coating the floor with a mop on acrylic emulsion finish to further protect and enhance the floor. The floor will typically need to be resealed twice per year. This procedure can be performed within a few hours.

Reztec is made from a blend of post consumer (recycled tires) and postindustrial waste rubber and virgin rubber granules, held together with a urethane binder. This blend is randomly mixed and heated in a cylindrical mold. After the heating process is complete, the cylinder (log) of Reztec is cut into the desired thickness utilizing a circular blade (knife) that “peels” the log. Since Reztec contains old tire waste, and this waste may include impurities such as metal and stones, the cutting blade can get nicked during the “peeling” process and this results in visible knife marks on the surface. These knife marks are inherent and not considered defects. The marks show more in colors with a high percentage of black. Also inherent to the product are shade variations due to the random mixing process and the urethane binder is subject to darkening and yellowing when exposed to sunlight.

Reztec’s durability is due to the high strength of the rubber as well as the fact that rubber resists scratches and gouges due to its resilience. To further improve the wear characteristics, Expanko has formulated Reztec to have the highest density of any comparable product on the market. Reztec exceeds all standards for recycled rubber flooring. Its high level of durability, natural texture and functional benefits provide an attractive surface that can be used in a wide range of areas. From cafeterias to retail stores and sports facilities, Reztec will provide years of problem free service. Reztec is warranted for five years against manufacturing defects. Complete warranty information is available (*Document ID: 334*).

For more information Expanko visit our website at www.expanko.com.