



REZTEC AND REZTEC CHUNKS RUBBER FLOORING

MATERIAL SAFETY DATA SHEET

TECHNICAL SUPPORT 800.345.6202

CHEMICAL NAME	DIPHENYLMETHANE DIISOCYANATE (MDI) MODIFIED
TRADE NAME	REZTEC RUBBER FLOORING
HAZARDOUS INGREDIENTS	N/A
PHYSICAL DATA	
BOILING POINT	N/A
SPECIFIC GRAVITY (H ₂ O=1):	0.9
VAPOR PRESSURE (MM HG.):	N/A
PERCENT, VOLATILE BY VOLUME	(%)
VAPOR DENSITY (AIR=1):	N/A
EVAPORATION RATE (____=1):	N/A
SOLUBILITY IN WATER:	N/A
APPEARANCE AND ODOR:	BLACK/ WITH SLIGHT ODOR
SPECIAL PROTECTION INFORMATION	
RESPIRATORY PROTECTION:	N/A
VENTILATION: LOCAL EXHAUST	N/A
MECHANICAL	N/A
PROTECTIVE GLOVES:	N/A
EYE PROTECTION:	N/A
OTHER PROTECTIVE EQUIPMENT:	N/A
SPECIAL PRECAUTIONS	
TO BE TAKEN IN HANDLING AND STORAGE:	AVOID CONTACT WITH FLAME, AND EXCESSIVE RADIANT HEAT
FIRE AND EXPLOSION HAZARD DATA	
FLASH POINT (METHOD USED)	N/A
FLAMMABLE LIMITS:	N/A
EXTINGUISHING MEDIA:	CO ₂ , DRY CHEMICAL, COPIOUS
SPECIAL FIRE FIGHTING PROCEDURES:	WEAR RESPIRATOR TO AVOID SMOKE INHALATION.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	NONE
HEALTH HAZARD DATA	
THRESHOLD LIMIT VALUE:	NONE ESTABLISHED
EFFECTS OF OVEREXPOSURE:	NONE ESTABLISHED
EMERGENCY & FIRST AID PROCEDURES:	INGESTION CALL PHYSICIAN
REACTIVITY DATA	
STABILITY:	STABLE
CONDITIONS TO AVOID:	N/A
HAZARDOUS DECOMPOSITION PRODUCTS:	CO ₂ , CO, NITROGENOUS COMPOUNDS
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR
SPIIL OR LEAK PROCEDURES:	

REZTEC AND REZTEC CORKS RUBBER FLOORING
MATERIAL SAFETY DATA SHEET

STEPS TO BE TAKEN N/A
MATERIAL TO BE SPILLED: N/A

WASTE DISPOSAL METHOD: APPROVED LANDFILL OR
RECYCLING/REGRANULATION

For more information about Expanko visit our website at www.expanko.com or Expanko at 800.345.6202. *Expanko since 1945.*