



Expanko Resilient Flooring
1000 East Park Avenue | Maple Shade, NJ 08052
800.345.6202 | sales@expanko.com | www.expanko.com



MATERIALS SAFETY DATA SHEET - JET SERIES

TECHNICAL SUPPORT 800.345.6202

CHEMICAL NAME: DIPHENYLMETHANE DIISOCYANATE
(MDI) MODIFIED
TRADE NAME: REZTEC RUBBER FLOORING - JET SERIES

HAZARDOUS INGREDIENTS

PHYSICAL DATA: N/A
BOILING POINT: N/A
SPECIFIC GRAVITY (H₂O=1): 0.9
VAPOR PRESSURE (MM HG.): N/A
PERCENT, VOLATILE BY VOLUME: (%)
VAPOR DENSITY (AIR=1): N/A
EVAPORATION RATE (____=1): N/A
SOLUBILITY IN WATER: N/A
APPEARANCE AND ODOR: BLACK/ WITH SLIGHT ODOR

SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: N/A
VENTILATION - LOCAL EXHAUST: N/A
MECHANICAL: N/A
PROTECTIVE GLOVES: N/A
EYE PROTECTION: N/A
OTHER PROTECTIVE EQUIPMENT: N/A

SPECIAL PRECAUTIONS

TO BE TAKEN IN HANDLING AND STORAGE: AVOID CONTACT WITH FLAME AND EXCESSIVE RADIANT HEAT

FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): N/A
FLAMMABLE LIMITS: N/A
EXTINGUISHING MEDIA: CO₂, DRY CHEMICAL, COPIOUS
SPECIAL FIRE FIGHTING PROCEDURES: WEAR RESPIRATOR TO AVOID SMOKE INHALATION
UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: NONE ESTABLISHED
EFFECTS OF OVEREXPOSURE: NONE ESTABLISHED

EMERGENCY & FIRST AID PROCEDURES:

INGESTION CALL PHYSICIAN

REACTIVITY DATA

STABILITY:

STABLE

CONDITIONS TO AVOID:

N/A

HAZARDOUS DECOMPOSITION PRODUCTS:

CO₂, CO, NITROGENOUS COMPOUNDS

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR

SPILL OR LEAK PROCEDURES:

N/A

STEPS TO BE TAKEN

N/A

MATERIAL TO BE SPILLED:

N/A

WASTE DISPOSAL METHOD:

APPROVED LANDFILL

For more information visit www.expanko.com or call 800-345-6202.