SCS Global Services does hereby certify that an independent assessment has been conducted on behalf of:

Loba-Wakol LLC

2732 Hwy 74 West, , Wadesboro, NC, United States

For the following product(s):

See Addendum

The product(s) meet(s) all of the necessary qualifications to be certified for the following claim(s):

FloorScore[®]

Indoor Air Quality Certified to SCS-EC10.3-2014 v4.0

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom, private office, and single-family residence parameters when modeled as Flooring. Also, conforms to the SCAQMD Rule 1168 - Adhesive and Sealants (October 2017); Hong Kong Air Pollution Control (VOC) Regulation.

Standard Product Application Amount: 1800 g/m²

Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m³ (in compliance with CDPH/EHLB Standard Method v1.2-2017)

Methylene Chloride and Perchloroethylene are not intentionally added to certified products.

Registration # SCS-FS-05759

Valid from: November 1, 2020 to October 31, 2021

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore®







Stanley Mathuram, PE, Vice President SCS Global Services 2000 Powell Street, Ste. 600, Emeryville, CA 94608 USA



Certification Addendum

Loba-Wakol LLC

Certification: Registration # SCS-FS-05759 | Valid from: November 1, 2020 to October 31, 2021

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, http://www.scsglobalservices.com/certified-green-products-guide.

Addendum FloorScore®

Indoor Air Quality Certified to SCS-EC10.3-2014 v4.0

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom, private office, and single-family residence parameters when modeled as Flooring. Also, conforms to the SCAQMD Rule 1168 - Adhesive and Sealants (October 2017); Hong Kong Air Pollution Control (VOC) Regulation.

Standard Product Application Amount: 1800 g/m²

Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m³ (in compliance with CDPH/EHLB Standard

products Guide, http://www.scsglobalservices.com/certified-green-products-quide.

Adhesives:

WAKOL D 965 Tackifier Dispersion, WAKOL D 3035 Special Primer, WAKOL D 3045 Special Primer, WAKOL D 3125, WAKOL D 3307 PVC Adhesive, WAKOL D 3317 PVC Adhesive, WAKOL D 3318 MultiFlex, WAKOL D 3319 LVT Flooring Adhesive, WAKOL D 3320 PVC Adhesive, WAKOL D 3330 Luxury Vinyl Tile Adhesive, WAKOL D 3360 VersaTack, WAKOL D 3513 Precoat for Cork Flooring, WAKOL D 3540 Cork Flooring Adhesive, WAKOL DL 3365 StarLeit, WAKOL MS 228 Ready-to-lay Parquet Adhesive, WAKOL MS 230 Parquet Adhesive, WAKOL MS 232 Parquet Adhesive, WAKOL MS 260 Parquet Adhesive, WAKOL MS 262 Parquet Adhesive, WAKOL MS 290 Parquet Adhesive, WAKOL MS 330 Moisture Barrier, WAKOL MS 550 PVC and Rubber Adhesive, WAKOL PU 270 Polyurethane Adhesive, WAKOL PU 280 Moisture Barrier, WAKOL D 3120 PVC Adhesive, WAKOL MS 552 PVC and Rubber Adhesive

