

Declare. SM

Sereniti Rubber Flooring Expanko Resilient Flooring

Final Assembly: Sherbrooke, Québec, Canada

Life Expectancy: 20 Year(s)

End of Life Options: Landfill (100%)

Ingredients:

Filler: Clay; Aluminum hydroxide; **Polymer:** Styrene-butadiene copolymers; **Curing Agent:** Alkanes, C14-17, chloro; Cork; Zinc oxide; 2-Benzothiazolesulfenamide, N-(1,1-dimethylethyl)-; 2H-Benzimidazole-2-thione, 1,3-dihydro-4(or 5)-methyl-, zinc salt (2:1); Antimony oxide (Antimony trioxide); Chlorinated paraffins (CPs); Curing agent; Morpholine, 4,4'-dithiobis-; Phthalic Anhydride; Stearic Acid; Sulfur Elemental; **Pigment:** Titanium dioxide; C.I. Pigment Blue 29; C.I. Pigment Green 7; C.I. Pigment Yellow 42; Carbon black; Diiron Trioxide; Red pigment; **Resin:** Petroleum resins

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

EPK-0001
EXP. 01 MAY 2021
Original Issue Date: 2017